



MX40-32A-P-S-PP

3.000 - 6.000 l/h Discs, cartridges

Typical applications
Plating and process industry

Features

- Service friendly, ideal cleaning access height
- Magnetic drive pump
- Filter chamber with welded bottom (no seal)
- Discs (thin/thick paper, cloth) or cartridges
- All PP construction
- Max. temperature PP 80°C
- Bottom-out or top-out model
- Choice of slurry tank for carbon treatment, mixing and priming
- Unions for rigid piping (PP or CPVC sockets)
- Standard with 3 phase motor, thermal overload switch, lead without plug, pressure gauge, air release and drain valve

Options

- Hose connection
- Dry run protection
- Contact manometer
- Single open end cartridges
- Slurry tank
- Sealpump
- Viton



M15-31A-K-PP

Filter Systems series 3

www.hendor.com

Pump	l/h	kW*	Union (d/DN) In Out	Hose In Out	Type	Chamber	Medium	Slurrytank	Material	
Magnetic drive	3000	0,18	32/25 25/20	1 1/4" 1"	M15	31A	K/P	 6 liter 13 liter	PP-EPDM	
	4000	0,18	32/25 25/20	1 1/4" 1"	MX40	32A				
	6000**	0,25	32/25 32/25	1 1/4" 1 1/4"	MX60					
					Selection:	MX40	32A	P	S	PP

** Only with 32A filter chamber

K = cartridges



Qty x L

31A-K = 3 x 10"
32A-K = 3 x 20"

P = discs



Qty OD/ID m²

31A-P = 32 x 136/32 0,4
32A-P = 65 x 136/32 0,9

* For 3-phase motors < 220V the indicated motor will be one size bigger.