

# 1001 WALL MOUNT SENSOR



**To Order :** Please specify the complete assembly, indicate the code letter or value for each option.

	Head Type	U-Length	Sensor OD	Sheath	Calibration	Junction	Transmitter	Scale Range	Options
1001	WMCA								
	1	2	3	4	5	6	7	8	9

**1. TERMINAL HEAD**

WMCA Default

**2. U - LENGTH**

eg - 8" or 200mm

**3. SENSOR OD**

eg - 3/16" or 5mm

**4. SENSOR SHEATH MATERIAL**

S4 SS304  
S6 SS316

**5. SENSOR CALIBRATION**

J Iron ® / Constantan ®, 4°C to 40°C Maximum  
K Chromel ® / Alumel ®, 4°C to 40°C Maximum  
T Copper ® / Constantan ®, 4°C to 40°C Maximum  
E Chromel ® / Constantan®, 4°C to 40°C Maximum  
PL Pt100 Ohms, 4°C to 40°C Maximum

**6. SENSOR JUNCTION**

SG Simplex, Grounded  
SU Simplex, Ungrounded  
SE Simplex, Exposed  
DG Duplex, Grounded  
DUC Duplex, Ungrounded, Common  
DUI Duplex, Ungrounded, Isolated  
DE Duplex, Exposed

**7. TRANSMITTER**

0 None  
ST Standard  
HC HART Compatible  
Output 4-20 mA - Default

**8. SCALE RANGE**

eg - -4°C / 35°C

**9. OPTIONS**

2W 2 Wire - Pt100 Ohms Sensor  
4W 4 Wire - Pt100 Ohms Sensor

