

# 1101 RTD METAL INSERT



To Order : Please specify the complete assembly, indicate the code letter or value for each option.

1101	Terminals	U-Length	Sensor OD	Sheath	Calibration	Element	Options
	1	2	3	4	5	6	7

**1. TERMINALS**

- O 6" PFA®, AWG-24S Lead Wire
- DP DIN Form B Plate, 6" PFA®, AWG-24S Lead Wire, Singles
- DPC DIN Form B With Ceramic Block

**2. U - LENGTH**

- eg - 8" or 200mm

**3. SENSOR OD**

- eg - 3/16" or 5mm

**4. SENSOR SHEATH MATERIAL**

- S4 SS304
- S6 SS316

**5. SENSOR CALIBRATION**

- PLA Pt100 Ohms, Low Temperature To 250°C, Class A
- PHA Pt100 Ohms, High Temperature To 650°C, Class A
- PHB Pt100 Ohms, High Temperature To 650°C, Class B
- HVB Pt100 Ohms, High Vibration, To 650°C, Class B

**6. SENSOR ELEMENT**

- SU Single, Ungrounded
- DUI Duplex, Ungrounded, Isolated

**7. OPTIONS**

- 2W 2 Wire - Pt100 Ohms Sensor
- 4W 4 Wire - Pt100 Ohms Sensor

