

# 1102 THERMOCOUPLE METAL INSERT



To Order : Please specify the complete assembly, indicate the code letter or value for each option.

1102	Terminals	U-Length	Sensor OD	Sheath	Calibration	Junction
	1	2	3	4	5	6

**1. TERMINALS**

- O 6" PFA®, AWG-24S Lead Wire
- DP DIN Form B Plate, 6" PFA®, AWG-24S Lead Wire, Singles
- DPC DIN Form B With Ceramic Block

**2. U - LENGTH**

- eg - 8" or 200mm

**3. SENSOR OD**

- eg - 3/16" or 5mm

**4. SENSOR SHEATH MATERIAL**

- S4 SS304
- S6 SS316

**5. SENSOR CALIBRATION**

- J Iron ® / Constantan ®
- K Chromel ® / Alumel ®
- T Copper ® / Constantan ®
- E Chromel ® / Constantan ®
- N Nicrosil ® / Nisil ®

**8. SENSOR JUNCTION**

- SG Simplex, Grounded
- SU Simplex, Ungrounded
- SE Simplex, Exposed
- DG Duplex, Grounded
- DUC Duplex, Ungrounded, Common
- DUI Duplex, Ungrounded, Isolated
- DE Duplex, Exposed

