

# 1201 RTD METAL PROBE SENSOR



To Order : Please specify the complete assembly, indicate the code letter or value for each option.

	Calibration	Element	U-Length	Sensor OD	Sheath	Termination	Type	Options
1201					S6			
	1	2	3	4	5	6	7	8

## 1. SENSOR CALIBRATION

PLA	Pt100 Ohms, Low Temperature To 250°C, Class A
PHA	Pt100 Ohms, High Temperature To 650°C, Class A
PHB	Pt100 Ohms, High Temperature To 650°C, Class B
HVB	Pt100 Ohms, High Vibration, To 650°C, Class B

## 2. SENSOR ELEMENT

SU	Single, Ungrounded
DUI	Duplex, Ungrounded, Isolated

## 3. U - LENGTH

eg - 8" or 200mm

## 4. SENSOR OD

18	1/8"
316	3/16"
14	1/4"

## 5. SENSOR SHEATH MATERIAL

S6	SS316
----	-------

## 6. TERMINATION

3MP	3-Pin Miniature Plug
3MS	3-Pin Miniature Socket

## 7. TYPE

TP	Thermoplastic, 200°C, Maximum
CE	Ceramic, 600°C, Maximum

## 8. OPTIONS

2W	2 Wire - Pt100 Ohms Sensor
4W	4 Wire - Pt100 Ohms Sensor

