

1202 THERMOCOUPLE METAL PROBE SENSOR



To Order : Please specify the complete assembly, indicate the code letter or value for each option.

1202	Calibration	Junction	U-Length	Sensor OD	Sheath	Termination	Type	Options
	1	2	3	4	5	6	7	8

1. SENSOR CALIBRATION

- J Iron ® / Constantan ®
- K Chromel ® / Alumel ®
- T Copper ® / Constantan ®
- E Chromel ® / Constantan ®
- N Nicrosil ® / Nisil ®

2. SENSOR JUNCTION

- SG Simplex, Grounded
- SU Simplex, Ungrounded
- SE Simplex, Exposed
- DG Duplex, Grounded
- DUC Duplex, Ungrounded, Common
- DUI Duplex, Ungrounded, Isolated
- DE Duplex, Exposed

3. U - LENGTH

- eg - 8" or 200mm

4. SENSOR OD

- 18 1/8"
- 316 3/16"
- 14 1/4"

5. SENSOR SHEATH MATERIAL

- S4 SS304
- S6 SS316
- A6 Alloy 600

6. TERMINATION

- 2MP 2-Pin Miniature Plug
- 2MS 2-Pin Miniature Socket

7. TYPE

- TP Thermoplastic, 200°C, Maximum
- CE Ceramic, 600°C, Maximum

8. OPTIONS

- HTE Hydrostatic Pressure Test, External

