

31528 SINGLE FLOAT, ANGLED LEVEL SWITCH



To Order : Please specify the complete assembly, indicate the code letter or value for each option.

| | Connection | Sheath | Floath Dia | Contact | Length, L1 | Length, L2 | Lead Wire | LW |
|-----------|------------|--------|------------|---------|------------|------------|-----------|----|
| 31528-AFS | | | 28 | | | | LW1 | |
| | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 |

1. INSTRUMENT CONNECTION

| | HEX SIZE |
|-----|----------|
| M16 | 7/8" |
| M20 | 1" |

2. SHEATH MATERIAL

| | |
|----|-------|
| S4 | SS304 |
| S6 | SS316 |

3. FLOAT DIAMETER

| | SIZE | SHEATH OD |
|----|-------|-----------|
| 28 | Ø28mm | 5/16" |

SWITCHING CAPACITY

| | |
|---|----------------------|
| D | 50W / 240V VAC, SPST |
| K | 20W / 240 VAC, SPDT |

4. CONTACT FORM

| | |
|----|----------------------|
| AD | Normally Open, SPST |
| BD | Normally Close, SPST |
| CK | SPDT |

5. LENGTH, L1

eg - 8" or 200mm

6. LENGTH, L2

eg - 8" or 200mm

7. LEAD WIRE

LW1 AWG24, STRANDED, PVC-PVC

8. LW - LEAD LENGTH

eg - 1000mm

