

# 4201 2 LEVEL VERTICAL FLOAT SWITCH WITH BARREL HOUSING



To Order : Please specify the complete assembly, indicate the code letter or value for each option.

	Connection	Rating	Type	Sheath	Float Dia	Contact-1	Length, L1	Contact-2	Length, L2	C to C	Length, TL
	1	2	3	4	5	6	7	8	9	10	11
4201-VFS	2F	5K	RF	S4	45						

**1. INSTRUMENT CONNECTION**

2F 2" Flange

**2. STANDARD**

5K JIS 5K

**3. TYPE**

RF Raised Face

**4. SHEATH MATERIAL**

S4 SS304

**5. FLOAT DIAMETER**

	SIZE	SHEATH OD
45	Ø 45mm	1/2"

**SWITCHING CAPACITY**

D 50W / 240V VAC, SPST  
K 20W / 240 VAC, SPDT

**6. CONTACT-1 FORM**

AD Normally Open, SPST  
BD Normally Close, SPST  
CK SPDT

**7. LENGTH, L1 - FLOAT LEVEL**

eg - 2000mm

**8. CONTACT-2 FORM**

AD Normally Open, SPST  
BD Normally Close, SPST  
CK SPDT

**9. LENGTH, L2 - FLOAT LEVEL**

eg - 1000mm

**10. C TO C - CENTER TO CENTER**

eg - -

**11. LENGTH, TL - TOTAL**

eg - Max. 5000mm

