

1560 TUBE SKIN SENSOR



To Order : Please specify the complete assembly, indicate the code letter or value for each option.

1560	Head Type	Extension	A-Length	Calibration	Junction	U-Length	Sensor OD	Sheath	Weld Pad	Options
	1	2	3	4	5	6	7	8	9	10

1. TERMINAL HEAD

- 0 No Head, 6" Lead Wire With 1/2" NPT Head Connection.
- CA Cast Aluminum
- CI Cast Iron
- CSS Cast Stainless - SS316

2. NECK EXTENSION

- NS Nipple, SS304
- NUNS Nipple Union Nipple, SS304

3. A - LENGTH

- eg - 6" or 150mm

4. SENSOR CALIBRATION

- J Iron ® / Constantan ®
- K Chromel ® / Alumel ®
- T Copper ® / Constantan ®
- E Chromel ® / Constantan ®
- N Nicrosil ® / Nisil ®

** For Special Limits, Repeat Sensor Code, eg KK

5. SENSOR JUNCTION

- SG Simplex, Grounded
- SU Simplex, Ungrounded
- DG Duplex, Grounded
- DUC Duplex, Ungrounded, Common
- DUI Duplex, Ungrounded, Isolated

6. U - LENGTH

- eg - 590" or 15,000mm

7. SENSOR OD

- 18 1/8"
- 316 3/16"
- 14 1/4"

8. SENSOR SHEATH MATERIAL

- S4 SS304
- S6 SS316
- A6 Alloy 600

9. WELD PAD

- WPF Weld Pad, Flat, 1" x 1" x 1/8" Thick
- WPL Weld Pad, Longitudinal, 1" x 1" x 1/8" Thick

10. OPTIONS

- EP Expansion Loop

