

# 1571 PIPE CLAMP PROBE WITH LEAD WIRE



To Order : Please specify the complete assembly, indicate the code letter or value for each option.

1571	Calibration	Junction	U-Length	Sensor OD	Sheath	Lead Wire	LW	Termination	Type	Pipe Size	Options
	1	2	3	4	5	6	7	8	9	10	11

**1. SENSOR CALIBRATION**

- J Iron ® / Constantan ®
- K Chromel ® / Alumel ®
- T Copper ® / Constantan ®

**2. SENSOR JUNCTION**

- SG Simplex, Grounded
- SU Simplex, Ungrounded

**3. U - LENGTH**

- eg - 8" or 200mm

**4. SENSOR OD**

- 18 1/8"

**5. SENSOR SHEATH MATERIAL**

- S4 SS304
- A6 Alloy 600

**6. LEAD WIRE**

- LW2 AWG24, Stranded, PFA-PFA®
- LW3 AWG24, Stranded, FG-FG
- LW4 AWG24, Stranded, FG-SSOB

**7. LW - LEAD LENGTH**

- eg - 1000mm

**8. TERMINATION**

- 0 None, with Spade Lugs
- 2MP 2-Pin Miniature Plug
- 2MS 2-Pin Miniature Socket

**9. TYPE**

- 0 None
- TP Thermoplastic, 200°C, Maximum

**10. PIPE SIZE**

- 1 1" Pipe
- 112 1-1/2" Pipe
- 2 2" Pipe
- 212 2-1/2" Pipe

**11. OPTIONS**

- 0 None
- AR5 Ø5mm SS Armour Conduit, Square Locked
- AR38 Ø3/8" SS Armour Conduit, Square Locked

