

1578 PIERCING PROBE SENSOR



To Order : Please specify the complete assembly, indicate the code letter or value for each option.

Calibration	U-Length	Sensor OD	Sheath	Lead Wire	LW	Termination	Type	Options
1578	140	4	S6				TP	
1	2	3	4	5	6	7	8	9

1. SENSOR CALIBRATION

- J Iron ® / Constantan ®
- K Chromel ® / Alumel ®
- T Copper ® / Constantan ®
- PLA Pt100 Ohms, Low Temperature To 250°C, Class A

2. U - LENGTH

- 140 140mm

3. SENSOR OD

- 4 4mm

4. SENSOR SHEATH MATERIAL

- S6 SS316

5. LEAD WIRE

- LW7 AWG24, Solid, PFA-PFA®
- LW8 AWG28, Solid, PFA-PFA®

6. LW - LEAD LENGTH

- eg - 1000mm

7. TERMINATION

- 2MP 2-Pin Miniature Plug
- 2MS 2-Pin Miniature Socket
- 3MP 3-Pin Miniature Plug
- 3MS 3-Pin Miniature Socket

8. TYPE

- TP Thermoplastic, 200°C, Maximum

9. OPTIONS

- 0 None
- AR5 Ø5mm SS Armour Conduit, Square Locked
- AR38 Ø3/8" SS Armour Conduit, Square Locked

